#### **ANNEX 2**

## RESOLUTION MSC.475(102) (adopted on 11 November 2020)

## AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution MSC.391(95), by which it adopted the International Code of Safety for Ships Using Gases or Other Low-flashpoint Fuels ("the IGF Code"), which has become mandatory under chapter II-1 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"),

RECALLING FURTHER article VIII(b) and regulation II-1/2.28 of the Convention concerning the procedure for amending the IGF Code,

HAVING CONSIDERED, at its 102nd session, amendments to the IGF Code proposed and circulated in accordance with article VIII(b)(i) of the Convention,

- 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the IGF Code, the text of which is set out in the annex to the present resolution;
- DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the amendments shall be deemed to have been accepted on 1 July 2023 unless, prior to that date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified their objections to the amendments;
- 3 INVITES Contracting Governments to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2024 upon their acceptance in accordance with paragraph 2 above;
- 4 REQUESTS the Secretary-General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;
- 5 REQUESTS ALSO the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization, which are not Contracting Governments to the Convention.

### **ANNEX**

# DRAFT AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

## PART A-1 SPECIFIC REQUIREMENTS FOR SHIPS USING NATURAL GAS AS FUEL

#### **6 – FUEL CONTAINMENT SYSTEM**

### 6.7 Regulation for pressure relief system

1 Regulation 6.7.1.1 is replaced by the following:

"All fuel storage tanks shall be provided with a pressure relief system appropriate to the design of the fuel containment system and the fuel being carried. Fuel storage hold spaces, interbarrier spaces and tank connection spaces, which may be subject to pressures beyond their design capabilities, shall also be provided with a suitable pressure relief system. Pressure control systems specified in 6.9 shall be independent of the pressure relief systems."

#### 11 - FIRE SAFETY

The following new regulation 11.8 is added after existing regulation 11.7:

### "11.8 Regulation for fuel preparation room fire-extinguishing systems

For ships constructed on or after 1 January 2024, fuel preparation rooms containing pumps, compressors or other potential ignition sources shall be provided with a fixed fire-extinguishing system complying with the provisions of SOLAS regulation II-2/10.4.1.1 and taking into account the necessary concentrations/application rate required for extinguishing gas fires."

### PART B-1

### 16 - MANUFACTURE, WORKMANSHIP AND TESTING

## 16.3 Welding of metallic materials and non-destructive testing for the fuel containment system

- 3 Regulation 16.3.3.5.1 is replaced by the following:
  - ".1 tensile tests: cross-weld tensile strength is not to be less than the specified minimum tensile strength for the appropriate parent materials. For materials such as aluminium alloys, reference shall be made to 6.4.12.1.1.3 with regard to the regulations for weld metal strength of under-matched welds (where the weld metal has a lower tensile strength than the parent metal). In every case, the position of fracture shall be recorded for information:"

\*\*\*